



# EFFLUENT PUMPS

HUNG PUMP GROUP

## Features:

- IP68 protection and F class insulation.
- Built in thermal overload protection.
- With double mechanical seal design.
- Low temperature rise for long service life.
- Use closed-type impeller design, enable the pump to have high head and strong suction functions.


## Applications:

- Civil engineering & construction.
- Agriculture and irrigation at high mountain slope.
- Drainage of drain wells.
- Fountains for gardening & landscape area.
- Water supply equipments for high places.

## KSH Series



## PERFORMANCE CURVE



# KSH Series



## CONSTRUCTION

NO.	NAME	MATERIAL
1	Motor casing	SUS304
2	Pump casing	FC25
3	Upper cover	FC200
4	Bearing upper cover	FC200
5	Impeller	* PLASTIC OR BRASS
6	Seal cover	FC200
7	Diffuser	FC200
8	Flange	FC200
9	Handle	SUS 410
10	Stator	SILICON STEEL
11	Rotor & shaft	SUS 410
12	Capacitor	PP
13	Upper bearing	CNM5K
13-1	Lower bearing	CNM5K
14	Strainer	SUS304/FC200
15	Cable gland	NBR
16	Discharge adapter	ABS
17	Mechanical seal	** CA / CE + CA / CE
18	Oil seal	NBR
18-1	Oil seal	NBR
19	Packing	NBR
19-1	Packing	NBR

Remark: \*KSH 05 impeller is made of plastic.  
 \*\* 1HP and above is equipped with double mechanical seal.

## SPECIFICATION

Type	Output		Discharge		Rated		Maximum		Weight	Dimension		
					Head	Capacity	Head	Capacity				
	HP	kW	mm	Inch	M	LPM	M	LPM		Kg	L(mm)	W(mm)
KSH-05	1/2	0.4	40	1 1/2"	10	80	18	120	16	290	168	422
KSH-10	1	0.75	40	1 1/2"	15	100	21	200	29	283	227	465
KSH-20	2	1.5	50	2"	15	180	25	320	32	283	227	484
KSH-30	3	2.2	50	2"	18	250	30	420	42	395	250	510
KSH-50	5	3.7	80	3"	20	300	35	550	50	455	290	585

Remark: KSH-05A/10A/20A are equipped with float switch.



## Hung Pump Group

16 Lien-Ming Street, Ba-De City 334,  
 Taoyuan, Taiwan  
 TEL:(886) -3-371-3969  
 FAX:(886) -3-371-3960  
 E-Mail: hungpump@ms9.hinet.net